



HCBP

CARBON BLACK PRESS

Hydraulic press for the preparation of carbon black samples according to ASTM D3493 and ISO 4656

The HCBP is an hydraulic press engineered for the specific use of compressing carbon black according to the ASTM standard D3493 and ISO 4656 for the determination of COAN number. The HCBP is designed to be placed and operated in a chemical lab with a compact design and with particular attention on HSE aspects. The compressing chamber is a confined area accessible by opening a transparent door.

On the back of the machine, a shutter allows the user to connect the system to the exhaust system of the lab (diam. 100 mm).

The press is set up to give on the sample the target pressure of 165 MPa. An analogic pressure gauge allows the operator to control the pressure of the system while compressing.

A digital cycle counter helps the operator to keep count of the compression cycles already done.

Key features

- Compact design
- Easy to clean
- Ready for connection to the exhaust system
- Compressing area enclosed and safe
- Pressure gauge for visual control of pressure during compression
- Digital cycle counter

Customer satisfaction promise

We offer worldwide installation and training services by our experienced engineers and technicians.

Contact our sales & service team for more information: sales@hitec.lu

Visit our online catalog for more information:




shop.hitec.lu/product/hcbp/

HITEC Luxembourg S.A.
49, rue du Baerendall L-8212 Mamer
T +352 49 84 78 - 1 | F +352 40 13 03
info@hitec.lu | www.hitec.lu

Follow us on [f](#) | [in](#) | [t](#) | [@](#)

HCBP CHARACTERISTICS

Dimension & supply

 Power supply	400 V, 50/60 Hz, 50 A
 Dimensions	809 x 758 x 1908 mm (W x D x H)
 Weight	325 kg

Hydraulic system

Maximum pressure of the hydraulic system	210 Bar
Pressure applied on the sample (fixed as per related standards)	165 MPa
Piston speed – compression phase:	10 mm/s
Oil tank capacity:	5 lt

Compression chamber

Internal diam	31.8 mm
Available volume	73.9 cm ³

Safety

- CE marking
- SGS-USTC certified

Options

Loadcell 28T with display for pressure control
Higher volume compression chamber (internal diameter 42 mm - coming soon)

All product, product specifications and data are subject to change without notice to improve reliability, function or design.

